



TYPICAL SECTION

NOTES

1. THE BARRIER AND FOOTER SHALL BE CAST SEPARATELY USING THE FIXED FORM OR THE SLIP FORM CONSTRUCTION METHOD USING CONCRETE MIX NO.6 (4500 PSI).
2. THE BARRIER FOOTER AND BARRIER FORMS SHALL BE REMOVED BEFORE PLACING PAVEMENT.
3. WHEN THE BARRIER IS CONSTRUCTED USING THE SLIP FORM METHOD DIAGONAL NO. 4 REINFORCEMENT BARS ARE REQUIRED. SEE STD. MD 648.44-04.
4. ALL REINFORCEMENT BARS, INCLUDING ENDS, SHALL BE EPOXY COATED. ALL BAR LAPS TO BE 30 BAR DIAMETERS. TIE BARS TOGETHER. ALL REINFORCEMENT BARS SHALL BE ASTM A 615, GRADE 60.
5. SPACING OF CONTRACTION JOINTS SHALL BE 20 FEET REGARDLESS OF CONSTRUCTION METHOD.
6. COST OF CONCRETE FOOTER, ALL REINFORCEMENT, AND EXCAVATION SHALL BE INCIDENTAL TO THE CONTRACT UNIT PRICE PER LINEAR FOOT FOR 42 INCH F SHAPE CONCRETE MEDIAN TRAFFIC BARRIER BIFURCATED 1 FOOT 6 INCHES TO 4 FEET 0 INCHES.
7. WHEN THE BARRIER IS CONSTRUCTED ON EXISTING RIGID PAVEMENT THE COST OF ALL REINFORCEMENT, DRILLED HOLES, GROUT, LABOR, TOOLS, EQUIPMENT, ETC., SHALL BE INCIDENTAL TO THE PRICE PER LINEAR FOOT FOR THE ITEM SPECIFIED IN NOTE 6.
8. TOLERANCES IN DIMENSIONS SHOWN SHALL BE WITHIN 1/4".

SPECIFICATION 604	CATEGORY CODE ITEMS
APPROVED	<i>Kirk G. McCall</i> DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT
	APPROVAL • SHA REVISIONS
	APPROVAL 3-1-01
	REVISED 10-1-01
	REVISED
APPROVAL • FEDERAL HIGHWAY ADMINISTRATION	APPROVAL 3-28-01
REVISED	REVISED
REVISED	REVISED

Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
 STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES
42 INCH F SHAPE CONCRETE MEDIAN
TRAFFIC BARRIER BIFURCATED
1 FOOT 6 INCHES TO 4 FEET 0 INCHES
STANDARD NO. MD 648.44-02