



SIGN	DIME	VSION	S (IN	(INCHES)	
SIZE	А	В	С	D	
STD	BASED ON	PRODUCT	3	4-1/4	

TWO SIDED END TREATMENTS





ONE SIDED END TREATMENTS

NOTES

- 1. DELINEATION MUST MEET THE REQUIREMENTS IN MUTCD SECTIONS 2C.64 AND 2C.65.
 2. DELINEATION SHALL BE TYPE IX OR XI REFLECTIVE SHEETING WITH BLACK STRIPES ON FLUORESCENT YELLOW.
 3. WHEN PLACING SHEETING ON BARE METAL, METAL SHOULD BE CLEANED AS PER MANUFACTURER'S RECOMMENDATIONS
- PRIOR TO APPLICATION OF SHEETING.

 4. SHEETING SHOULD EXTEND TO TOP AND BOTTOM AND FULL WIDTH OF TERMINAL. SIZE MAY BE ADJUSTED AS NECESSARY TO FIT DIFFERENT MANUFACTURER'S TERMINALS.

 5. DELINEATION WILL BE INCIDENTAL TO THE APPROPRIATE TRAFFIC BARRIER END TREATMENT.

SPECIFICATION 606	N CATEGORY CODE ITEMS			MARYLAND DEPARTMENT OF TRANSPORTATION				
APPROVED TURNING OF HIGHWAY DEVELOPMENT		STATE HIGHWAY ADMINISTRATION STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES TRAFFIC BARRIER END TREATMENT AND CRASH CUSHION DELINEATION						
APPROVAL SHA APPROVAL FEDERAL REVISIONS HIGHWAY ADMINISTRATION								
APPROVAL 9- REVISED	20-19	APPROVAL REVISED	8-15-19	CRASH CUSHIO	N DELII	NEATION		
REVISED REVISED		REVISED REVISED		STANDARD NO.	MD	605.14		