



**NOTES:**

1. INSTALLATION SHALL BE PERFORMED PER MANUFACTURER'S RECOMMENDATIONS.
2. CORNER BOLTS AND HARDWARE SHALL BE AS APPROVED BY AASHTO AND PER MANUFACTURER'S RECOMMENDATIONS.
3. THE INSTALLATION SHALL MEET THE LATEST AASHTO BREAKAWAY REQUIREMENTS.
4. SPLICES SHALL NOT BE USED TO EXTEND THE HEIGHT OF A SIGN POST.
5. ONLY 2" SIGN SUPPORTS SHALL BE USED. SIGN POSTS GREATER THAN OR LESS THAN 2" ARE NOT PERMITTED.
6. FOR SHEET ALUMINUM ATTACHMENT, ALL BOLTS SHALL BE 3/8" F593 (18-8 TYPE 303-304) STAINLESS STEEL OR ANODIZED ALUMINUM HEX HEAD BOLT WITH WASHERS AND NUTS SPACED AT 12" MAXIMUM.
7. ALL SHEET ALUMINUM SIGNS 5' WIDE AND LARGER SHALL BE BRACED WITH TWO HORIZONTAL 2"x4" TREATED WOOD OR EQUAL, ATTACHED TO THE SUPPORTS. THE BOLT LENGTHS SHALL BE COORDINATED.

SPECIFICATION <b>802</b>	CATEGORY CODE ITEMS
APPROVED 	DIRECTOR - OFFICE OF TRAFFIC AND SAFETY
	APPROVAL • SHA REVISIONS
	APPROVAL 5-17-07
	REVISED
	REVISED

**Maryland Department of Transportation  
STATE HIGHWAY ADMINISTRATION**

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

**BREAKAWAY TUBULAR  
STEEL SIGN SUPPORTS**

STANDARD NO.

MD 802.04