

MD 213 IS ASSUMED TO RUN IN A NORTHSOUTH DIRECTION

MD 213 SB

MD 213 NB

WHITEHALL RD

CONOWINGO NO. 14876

APS NOTES:

- PUSH BUTTONS ARE TO BE LOCATED SO THAT THEY CAN BE ACTIVATED BY A PERSON IN A WHEELCHAIR REACHING LESS THAN 18" FROM A 60" X 60" LEVEL LANDING AREA WITH A CROSS SLOPE OF LESS THAN OR EQUAL TO 2%.
- THE 10' SEPARATION BETWEEN PUSH BUTTONS IS TO BE MEASURED FROM FACE OF PUSH BUTTON TO FACE OF PUSHBUTTON, NOT CENTER TO CENTER OF POLE.
- PUSH BUTTON ARROWS ARE TO BE PARALLEL TO THE CROSSING FOR WHICH THEY ARE INTENDED.
- LOCATION OF ACCESSIBLE PEDESTRIAN SIGNAL PUSHBUTTONS MUST MEET LOCATION REQUIREMENTS OF MUTCD SEC. 4E.09 AND FIG. 4E.2 AND THE NCHRP PUBLICATION, "ACCESSIBLE PEDESTRIAN SIGNALS: GUIDE TO BEST PRACTICE". IF NOT MET, THE CONTRACTOR IS TO STOP WORK ON PUSH BUTTON LOCATIONS UNTIL A DESIGN WAIVER IS OBTAINED, APPROVED BY THE DIRECTOR, OFFICE OF TRAFFIC AND SAFETY.
- APS WILL FUNCTION AS FOLLOWS:

TO CROSS MD 213 AT WHITEHALL RD.

- WHEN A PEDESTRIAN LOCATES AND PRESSES THE PUSHBUTTON FOR AN EXTENDED TIME, THE PUSHBUTTON UNIT WILL ANNOUNCE THE FOLLOWING MESSAGE:
"WAIT TO CROSS AUGUSTINE HERMAN WAIT."
- WHEN THE "WALK" PHASE BEGINS, THE MESSAGE WILL BE A RAPID TICK, WHICH WILL LAST FOR THE DURATION OF THE "WALK" PHASE.

TO CROSS WHITEHALL RD. AT MD 213

- WHEN A PEDESTRIAN LOCATES AND PRESSES THE PUSHBUTTON FOR AN EXTENDED TIME, THE PUSHBUTTON UNIT WILL ANNOUNCE THE FOLLOWING MESSAGE:
"WAIT TO CROSS WHITEHALL WAIT."
- WHEN THE "WALK" PHASE BEGINS, THE MESSAGE WILL BE A RAPID TICK, WHICH WILL LAST FOR THE DURATION OF THE "WALK" PHASE.

GEOMETRIC CONSTRUCTION DETAILS:

- INSTALL PARALLEL SIDEWALK RAMP (STANDARD NO. MD 655.12) (NOTE: ONE 24"x60" DETECTABLE WARNING SURFACE.)
- INSTALL PARALLEL SIDEWALK RAMP (STANDARD NO. MD 655.12) (NOTE: THREE 24"x60" AND ONE 24"x36" DETECTABLE WARNING SURFACES.)
- INSTALL STANDARD TYPE A COMBINATION CURB AND GUTTER (STANDARD NO. MD 620.02).
- INSTALL STANDARD TYPE A CURB (STANDARD NO. MD 620.02).
- BEGIN 12:1 RAMP
- BEGIN 48:1 LEVEL LANDING AREA.
- TIE IN RAMP WITH EXISTING SIDEWALK AT JOINT.
- TIE NEW CURB TO EXISTING CURB AT JOINT.
- REMOVE EXISTING SIDEWALK AND BACKFILL WITH SEED AND MULCH.
- INSTALL 4" STANDARD TYPE A CURB.

2 GREEN LINE REVISION, NO. 2 12/20/2011

TEDD APPROVAL

GEOMETRIC LEGEND	
---	EXISTING
---	PROPOSED

UTILITY LEGEND	
SD	STORM DRAIN
G	GAS MAIN
W	WATER MAIN
S	SEWER MAIN
E	ELECTRIC CABLES
A	AERIAL CABLES
T	TELEPHONE CABLES
F	FIBER-OPTIC

LEGEND SYMBOL	DESCRIPTION
⊙	48" SIGNAL POLE FOUNDATION
⊙	36" SIGNAL POLE FOUNDATION
⊙	24" PED POLE FOUNDATION
⊙	18" PED POLE FOUNDATION W/SIGN AND PUSHBUTTON
⊙	PED SIGN AND PUSHBUTTON
■	SIGNAL CABINET W/PAD
■	POWER PEDESTAL
■	HANDHOLE
---	CONDUIT RUN

GEOMETRIC LEGEND	DESCRIPTION
---	EXISTING SIDEWALK/CURB JOINT (APPROXIMATE)
■	NEW SIDEWALK AND ADA HANDICAP RAMP
■	NEW CONCRETE
■	SEED AND MULCH

<p>SHA STATE OF MARYLAND DEPARTMENT OF TRANSPORTATION STATE HIGHWAY ADMINISTRATION OFFICE OF TRAFFIC & SAFETY TRAFFIC ENGINEERING DESIGN DIVISION MD 213 (AUGUSTINE HERMAN HWY) AT WHITEHALL ROAD ELKTON, MD</p>			
GEOMETRIC PLAN SHEET			
SCALE 1" = 10'	ADVERTISED DATE 10/20/11	CONTRACT NO. XX6815185	
DESIGNED BY DM	COUNTY CECIL		
DRAWN BY DM	LOGMILE 07021317.85		
CHECKED BY JB	TMS NO. L056		
F.A.P. NO.	TOD NO.		
TS NO. 3323F	DRAWING - OF	SHEET NO. 2 OF 3	

BY: davidma