






MD 63 IS ASSUMED TO RUN IN A NORTH-SOUTH DIRECTION



SPECIAL NOTE:
INSTALL HANDHOLE WITH LONG DIMENSION PERPENDICULAR TO TRAVEL WAY FOR INSTALLATION OF NON-INVASIVE PROBES. EXTEND CONDUIT A MINIMUM OF 2 IN. AND MAXIMUM OF 3 IN. INTO HANDHOLE.

NOTE:
PHASES ASSOCIATED BY A DASHED LINE WILL OPERATE CONCURRENTLY. PHASES ASSOCIATED BY A SOLID LINE WILL NOT OPERATE CONCURRENTLY.



- CONSTRUCTION DETAILS**
- INSTALL CONCRETE FOUNDATION WITH A 16.5 FT. (15'-0" T) STEEL POLE WITH TWIN 60 FT. /50 FT. (CUT TO 30 FT.) MAST ARMS, TRAFFIC SIGNAL HEADS, SIGNS, OPTICOM DETECTOR EYES AND VIDEO DETECTION CAMERA MOUNTED ON MAST ARM. (INSTALL 1-2 IN. AND 1-4 IN. SCHEDULE 80, 90 DEGREE PVC ELECTRICAL CONDUIT BENDS IN POLE BASE).
 - INSTALL NEMA SIZE "6" BASE MOUNTED CONTROLLER AND CABINET WITH CONCRETE PAD. (INSTALL 2-2 IN. AND 2-4 IN. SCHEDULE 80, 90 DEGREE PVC ELECTRICAL CONDUIT BENDS IN CABINET BASE.)
 - INSTALL EMBEDDED METERED SERVICE PEDESTAL WITH 2-2 IN. AND 1-4 IN. SCHEDULE 80, 90 DEGREE PVC CONDUIT BENDS IN PEDESTAL BASE.
 - INSTALL HANDHOLE.
 - INSTALL NON-INVASIVE MICROLOOP PROBE SET WITH 500 FT. LEAD-IN IN PROPOSED 3 IN. CONDUIT. (TO BE PLACED IN THRU LANE ONLY).
 - INSTALL NON-INVASIVE MICROLOOP PROBE SET WITH 1,000 FT. LEAD-IN IN PROPOSED 3 IN. CONDUIT. (TO BE PLACED IN THRU LANE ONLY).
 - INSTALL 3 IN. PVC SCHEDULE 80 ELECTRICAL CONDUIT - BORED.
 - INSTALL 2 IN. PVC SCHEDULE 80 ELECTRICAL CONDUIT - TRENCHED.
 - INSTALL 3 IN. PVC SCHEDULE 80 ELECTRICAL CONDUIT - TRENCHED.
 - INSTALL 4 IN. PVC SCHEDULE 80 ELECTRICAL CONDUIT - TRENCHED.
 - INSTALL 4 IN. PVC SCHEDULE 80 ELECTRICAL CONDUIT - BORED.
 - INSTALL 4 IN. SCHEDULE 80, PVC ELECTRICAL CONDUIT - TRENCHED FOR PROPOSED UNDERGROUND ELECTRICAL SERVICE.
 - INSTALL 2 IN. SCHEDULE 80, PVC ELECTRICAL CONDUIT - BORED FOR PROPOSED UNDERGROUND ELECTRICAL SERVICE.
 - INSTALL 2 IN. SCHEDULE 80, PVC ELECTRICAL CONDUIT - TRENCHED FOR PROPOSED UNDERGROUND TELEPHONE SERVICE.
 - INSTALL 2 IN. SCHEDULE 80, PVC ELECTRICAL CONDUIT - BORED FOR PROPOSED UNDERGROUND TELEPHONE SERVICE.
 - INSTALL 5 IN. HEAT APPLIED, WHITE PERMANENT PREFORMED THERMOPLASTIC PAVEMENT MARKING.
 - INSTALL 5 IN. HEAT APPLIED, YELLOW PERMANENT PREFORMED THERMOPLASTIC PAVEMENT MARKING.
 - INSTALL HEAT APPLIED, WHITE PERMANENT PREFORMED THERMOPLASTIC PAVEMENT MARKING ARROW.
 - INSTALL 24 IN. HEAT APPLIED, WHITE PERMANENT PREFORMED THERMOPLASTIC PAVEMENT MARKING FOR STOP LINE.
 - USE EXISTING HANDHOLE.
 - USE EXISTING CONDUIT.
 - CUT, CLEAN, GALVANIZE AND CAP TRAFFIC SIGNAL STRUCTURE.
 - INSTALL W3-3 "SIGNAL AHEAD" SIGN (36 IN. x 36 IN.) WITH "NEW" PANEL AND FLAGS ON ONE 4 IN. x 6 IN. TREATED WOOD POST APPROXIMATELY 490 FT. IN ADVANCE OF THE INTERSECTION ON NORTHBOUND MD 63.
 - INSTALL W3-3 "SIGNAL AHEAD" SIGN (36 IN. x 36 IN.) WITH "NEW" PANEL AND FLAGS ON ONE 4 IN. x 6 IN. TREATED WOOD POST APPROXIMATELY 625 FT. IN ADVANCE OF THE INTERSECTION ON SOUTHBOUND MD 63.
 - REMOVE EXISTING PAVEMENT MARKINGS IN CONFLICT WITH PROPOSED PAVEMENT MARKINGS.
 - REMOVE EXISTING PAVEMENT MARKING ARROW.
 - REMOVE EXISTING PAVEMENT MARKINGS BEYOND STOPLINE.
 - INSTALL R5-1, R6-1(L) AND R6-1(R) SIGNS ON ONE 4 IN. x 4 IN. TREATED WOOD SUPPORT. (L=15')
 - REMOVE EXISTING R1-1 SIGN AND SUPPORT.

- GENERAL NOTES**
- ALL TRAFFIC SIGNAL FOUNDATIONS SHALL BE INSTALLED AT THE FINAL SIDEWALK OR CURB GRADE FOR CLOSED SECTIONS, HIGHEST ROADWAY PROFILE GRADE FOR OPEN SECTIONS, TO MEET CLEARANCES AS SPECIFIED IN MD 816.03, MD 818.01, MD 818.02, MD 818.04. THE CONTRACTOR SHALL VERIFY ULTIMATE GRADES PRIOR TO THE INSTALLATION OF ALL SIGNAL EQUIPMENT.
 - THE CONTRACTOR SHALL VERIFY ALL UNDERGROUND UTILITIES PRIOR TO INSTALLING PROPOSED SIGNAL EQUIPMENT. IF ANY UTILITY CONFLICTS SHOULD ARISE THE CONTRACTOR SHALL CONTACT THE PROJECT ENGINEER.
 - VIDEO CAMERA LOCATION / ALIGNING SHALL BE COORDINATED WITH THE SHA ENGINEER.
 - THE CONTRACTOR SHALL VERIFY ALL PROPOSED POLE AND CABINET LOCATIONS PRIOR TO INSTALLATION.
 - THE CONTRACTOR SHALL BE RESPONSIBLE FOR TERMINATING ALL SIGNAL CABLES TO THE APPROPRIATE TERMINALS AND PROPERLY LABEL EACH CABLE.
 - THE CONTRACTOR SHALL NOT CUT MAST ARM AS INDICATED ON PLANS UNTIL MAST ARM POLE LOCATION IS FINALIZED.
 - FOR FINAL PAVEMENT MARKINGS REFER TO THE PAVEMENT MARKING PLANS, OTHER THAN THOSE DETAILED ON THE PLAN. ALL PAVEMENT MARKINGS SHALL BE INSTALLED IN ACCORDANCE WITH MSHA STANDARDS.
 - INSTALL CONDUIT AND LOOP DETECTORS PRIOR TO THE INSTALLATION OF PAVEMENT MARKINGS. REFER TO SIGNING AND PAVEMENT MARKING PLANS FOR ADDITIONAL DETAILS.
 - REFER TO SHEET TSP-3 FOR DIMENSIONS OF SIGNAL EQUIPMENT AND PAVEMENT MARKINGS WITHIN INTERSECTION.

WR&A
Whitman, Reardon and Associates, LLP
Engineers, Architects and Planners
801 South Caroline Street
Baltimore, Maryland 21231
410-235-3450

GEOMETRIC LEGEND

— EXISTING
— PROPOSED

UTILITY LEGEND

SD—SD STORM DRAIN
G—G GAS MAIN
W—W WATER MAIN
S—S SEWER MAIN
E—E ELECTRIC CABLES
A—A AERIAL CABLES
T—T TELEPHONE CABLES
F—F FIBER-OPTIC

APPROVALS

TEAM LEADER: [Signature] 4/23/09
ASST. DIVISION CHIEF: [Signature] 4/23/09
DIVISION CHIEF: [Signature] 4/23/09
OFFICE DIRECTOR: [Signature] 4/23/09

REVISIONS

NO.	DESCRIPTION	DATE

SHA STATE OF MARYLAND
DEPARTMENT OF TRANSPORTATION
STATE HIGHWAY ADMINISTRATION
OFFICE OF TRAFFIC & SAFETY
TRAFFIC ENGINEERING DESIGN DIVISION
MD 63 (Greencastle Pike) and
Pilot Travel Center Exit

TRAFFIC SIGNALIZATION PLAN

SCALE 1" = 20' ADVERTISED DATE 4/24/2009 CONTRACT NO. XX4245185

DESIGNED BY S. Bloss COUNTY Washington
DRAWN BY S. Bloss LOGMILE 21006310.62
CHECKED BY N. Leary TIMS NO. J783
F.A.P. NO. TOD NO.

TS NO. TS-4716 DRAWING TSP-1 OF 3 SHEET NO. ## OF 3