

TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION

STEP 5 - TEMPORARY TRAFFIC CONTROL ACTIVITIES

1. PLACE CHANNELIZING DEVICES AT CORRECT SPACING TO FORM TERMINATION TAPER MOVING WITH THE FLOW OF TRAFFIC
2. INSTALL "END ROAD WORK" SIGN APPROXIMATELY 500' FROM LAST DEVICE IN LANE CLOSURE MOVING WITH THE FLOW OF TRAFFIC

STEP 6 - TEMPORARY TRAFFIC CONTROL ACTIVITIES

1. CLEANUP WORK SPACE REMOVING ALL DEBRIS, VEHICLES, ETC.
2. REMOVE CHANNELIZING DEVICES FROM END OF CLOSURE BACK TO WIDEST PART OF LANE CLOSURE TAPER AGAINST THE FLOW OF TRAFFIC

NOTE:


WHEN OPENING OR CLOSING A LANE ON FREEWAYS, EXPRESSWAYS, AND ROADWAYS WITH POSTED SPEEDS ≥ 55 MPH, A WORK VEHICLE SHALL BE CLOSELY FOLLOWED BY A PROTECTION VEHICLE (PV) DURING INSTALLATION AND REMOVAL OF TEMPORARY TRAFFIC CONTROL DEVICES. REFER TO 104.01-19C FOR APPROPRIATE PV DETAILS.

THERE SHALL BE A MINIMUM OF SEVEN CHANNELIZING DEVICES IN THE SHOULDER TAPER.

* REFER TO SIGN SPACING CHART (MD 104.01-02)

KEY:

- CHANNELIZING DEVICES
- SIGN SUPPORT
FACE OF SIGN
- DIRECTION OF TRAFFIC
- ARROW PANEL
- WORK VEHICLE
- APPROVED VEHICLE SAFETY LIGHT
- WORK SITE



NOT TO SCALE

SPECIFICATION	CATEGORY CODE ITEMS
APPROVED	<i>Cedric Wald</i> DIRECTOR - OFFICE OF TRAFFIC AND SAFETY
SHA State Highway Administration	APPROVAL • SHA REVISIONS
	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION
	APPROVAL 8-20-03
	APPROVAL 9-23-03
	REVISD 8-11-10
REVISD 8-20-14	
REVISD 8-11-14	
REVISD 9-15-15	
REVISD 8-13-15	

Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

INSTALLING LANE CLOSURE - STEP 5
REMOVING LANE CLOSURE - STEP 6

STANDARD NO. MD 104.06-03