



NOTES:

1. THE USE OF THE PENNANT SHALL BE INSTALLED ON G2-1(1) OR G2-1(2) TOWARDS THE COMPLETION OF A PROJECT, AS DIRECTED BY THE PROJECT ENGINEER.
2. MIN SIZE IS FOR USE WITH G2-1(2) AND STD SIZE IS FOR USE WITH G2-1(1).

* ALTERNATE MESSAGE MAY BE USED, AS DIRECTED BY THE PROJECT ENGINEER

SIGN SIZE	DIMENSIONS (INCHES)												
	A	B	C	D	E	F	G	H	J	K	L	M	N
MIN	63	12	1/2	4	2.9496	2.7696	4.2808	2	29.3292	2.1528	1-1/8	27	29.7192
STD	84	16	3/4	5-11/32	3.636	3-61/64	5.614	2-51/64	38.7948	3.1548	1-1/2	36	39-5/8

SIGN SIZE	DIMENSIONS (INCHES)													
	P	Q	R	S	T	U	V	W	X	Y	Z	AA	BB	
MIN	2-1/4	7	3	4-7/8	3-1/2	0.75	3/4	9	0.15	1.5	130	3.5D*	3.5C*	
STD	3	9-1/2	3.8808	6-11/32	4.7964	1	1	12	0.2	2	175	5D*	5C*	

REFERENCES

MdMUTCD SECTION - 6F.50

COLORS

LEGEND - BLACK

BACKGROUND - WHITE

APPROVED Tom Hicks (signature on file)
DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
MARYLAND STANDARD HIGHWAY SIGNS



APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION
APPROVAL 03/02/2009	APPROVAL
REVISED	REVISED
REVISED	REVISED
REVISED	REVISED

PENNANT

SIGN NUMBER

G2-1(5)