



NUMBER OF MAT WIDTHS TO BE NOTED ON PLANS.

WIDTH AS NOTED ON PLANS



11 GAUGE WIRE OR HEAVIER LATERAL SPACING OF STAPLES TO BE AT EDGE OF MAT, AT OVERLAP OF MATS AND AT BREAK IN GROUND OR MIDPOINT OF MAT WHERE NO BREAKS OCCUR FOR THAT MAT.

NOTE: MAT WIDTH IS 48" ± 1"
 SEE SPECIFICATIONS FOR "SOIL STABILIZATION MATTING" FOR DETAILS OF MAT.
 USE SEED MIX SPECIFIED.
 MULCH IS NOT REQUIRED.
 WHEN TOPSOIL IS SPECIFIED IN THE AREA ADJACENT TO THAT WHERE SOIL STABILIZATION MATTING IS TO BE CONSTRUCTED, IT SHALL ALSO BE PLACED AT THE SAME DEPTH IN THE AREA WHERE SOIL STABILIZATION MATTING IS REQUIRED, PRIOR TO THE INSTALLATION OF THE MATTING.

SPECIFICATION 709	CATEGORY CODE ITEMS	Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES SOIL STABILIZATION MATTING DRAINAGE DITCHES
APPROVED	 DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT	
	APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION
	APPROVAL 6-22-61	APPROVAL 9-28-61
	REVISED 10-1-01	REVISED 6-27-85
	REVISED	REVISED
STANDARD NO. MD 389.06		