



- ① 2" SUPERPAVE ASPHALT MIX 9.5mm OR 12.5mm FOR SURFACE, PG64S-22, LEVEL 2
- ② SUPERPAVE ASPHALT MIX 19.0mm OR 25.0mm FOR BASE, PG64S-22, LEVEL 2 (SEE NOTES 1 THROUGH 4)
- ③ 24" GRADED AGGREGATE BASE (FOUR LIFTS) FOR 30' CLOSEST TO BRIDGE OR 12" GRADED AGGREGATE BASE BEYOND 30' (TWO LIFTS).

**BRIDGE APPROACHES**

**NOTES**

- 1. LIGHT TRAFFIC ~ ADT < 10,000 VEHICLES/DAY. ASPHALT BASE LAYER SHALL BE 8" THICK.
- 2. MEDIUM TRAFFIC ~ ADT > 10,000 TO LESS THAN < 30,000 VEHICLES/DAY. ASPHALT BASE LAYER SHALL BE 10" THICK.
- 3. HEAVY TRAFFIC ~ ADT > 30,000 VEHICLE/DAY. ASPHALT BASE LAYER SHALL BE 12" THICK.
- 4. REFER TO SPECIFICATION 505.03.10 FOR MINIMUM AND MAXIMUM LIFT THICKNESSES.

<b>SPECIFICATION</b>	<b>CATEGORY CODE ITEMS</b>	<b>MARYLAND DEPARTMENT OF TRANSPORTATION</b> STATE HIGHWAY ADMINISTRATION  <b>STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES</b>  <b>BRIDGE APPROACH</b> <b>PAVEMENT SECTIONS</b>  <b>STANDARD NO.                      MD 580.09</b>
<b>APPROVED</b>		
<b>APPROVAL REVISIONS</b>	<b>APPROVAL FEDERAL HIGHWAY ADMINISTRATION</b>	
<b>APPROVAL</b> 2-25-16	<b>APPROVAL</b> 2-23-16	
<b>REVISED</b> 10-27-22	<b>REVISED</b> 8-26-22	
<b>REVISED</b>	<b>REVISED</b>	