


NOTES

1. ALL W-BEAM AND HARDWARE COMPONENTS ACCORDING TO AASHTO SPEC. M 180.
2. FOUNDATION TUBE SHALL BE MANUFACTURED USING ASTM A500B STEEL AND SHALL CONFORM TO ASTM A500 GRADE B MATERIAL.
3. ONE-SIDED DOWNSTREAM END TREATMENT (TYPE K) NOT TO BE USED WHERE THERE IS OPPOSING TRAFFIC WITHIN 30 FT. OF THE END TREATMENT.

SPECIFICATION 605	CATEGORY CODE ITEMS
APPROVED	 DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT
APPROVAL SHA REVISIONS	APPROVAL FEDERAL HIGHWAY ADMINISTRATION
APPROVAL 1-26-70	APPROVAL 11-5-70
REVISED 4-17-06	REVISED 4-5-06
REVISED 1-9-20	REVISED 12-23-19
REVISED 3-31-20	REVISED 3-30-20

MDOT MARYLAND DEPARTMENT OF TRANSPORTATION
STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES
TRAFFIC BARRIER W-BEAM ONE-SIDED
DOWNSTREAM END TREATMENT (TYPE K)

STANDARD NO. MD 605.10