


PLAN VIEW



ELEVATION VIEW

NOTES

1. THE USE OF THIS ANCHORAGE IS LIMITED TO ROADWAYS WITH POSTED SPEEDS OF 40 MPH OR LESS AND AADT LESS THAN 10,000.
2. ALL ITEMS (ANCHOR PLATE, CABLE, ROD, DRILLED HOLES, NUTS, BOLTS, ETC) NECESSARY FOR THE ANCHOR SHALL BE MEASURED AND PAID PER EACH OF "TRAFFIC BARRIER W-BEAM RADIUS ANCHORAGE TYPE L." TRAFFIC BARRIER END SECTION SHALL BE INCIDENTAL TO THIS PAY ITEM.
3. THE TYPE L ANCHORAGE IS PERMITTED WITHIN A SINGLE RUN OF TRAFFIC BARRIER AS SHOWN. IF A TYPE L ANCHORAGE IS USED, THE DOWNSTREAM END TREATMENT IS REQUIRED ON THE TRAFFIC BARRIER END ONLY IF WITHIN 30' OF OPPOSITE DIRECTION TRAFFIC.
4. THE GROUND STRUT AS SHOWN IN STD. MD 605.10 AND MD 605.10-01 IS NOT REQUIRED IN THE TYPE L ANCHORAGE.

SPECIFICATION 605	CATEGORY CODE ITEMS
APPROVED	<i>[Signature]</i> DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT
APPROVAL SHA REVISIONS	APPROVAL FEDERAL HIGHWAY ADMINISTRATION
APPROVAL 3-15-06	APPROVAL 4-5-06
REVISED 2-25-20	REVISED 2-24-20
REVISED 3-31-20	REVISED 3-30-20
REVISED 3-16-22	REVISED 2-24-22

MOT MARYLAND DEPARTMENT OF TRANSPORTATION
STATE HIGHWAY ADMINISTRATION

**STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES
TRAFFIC BARRIER W-BEAM
RADIUS ANCHORAGE (TYPE L)**

STANDARD NO. MD 605.13