

STRUCTURE MARK	L_D	H_D	POLE SIZE	TRUSS CHORD TUBE SIZE	TRUSS BRACING TUBE SIZE
C-35-28-A	35'-0"	28'-9"	24" O.D. x .438" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-35-30-A		30'-0"	24" O.D. x .438" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-35-32-A		32'-0"	24" O.D. x .438" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-35-34-A		34'-0"	24" O.D. x .469" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-35-36-A		36'-0"	24" O.D. x .469" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-35-26-B		26'-9"	24" O.D. x .344" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-28-B		28'-0"	24" O.D. x .344" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-30-B		30'-0"	24" O.D. x .344" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-32-B		32'-0"	24" O.D. x .344" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-34-B		34'-0"	24" O.D. x .375" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-36-B		36'-0"	24" O.D. x .375" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-32-C		32'-0"	24" O.D. x .50" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-35-32-D		32'-0"	24" O.D. x .375" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-28-E		28'-9"	24" O.D. x .562" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-35-30-E		30'-0"	24" O.D. x .562" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-35-32-E		32'-0"	24" O.D. x .562" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-35-34-E		34'-0"	24" O.D. x .562" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-35-36-E		36'-0"	24" O.D. x .625" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-35-26-F		26'-9"	24" O.D. x .406" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-28-F		28'-0"	24" O.D. x .406" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-30-F		30'-0"	24" O.D. x .406" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-32-F		32'-0"	24" O.D. x .438" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-34-F		34'-0"	24" O.D. x .438" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-35-36-F		36'-0"	24" O.D. x .469" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-28-A	40'-0"	28'-9"	24" O.D. x .469" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-40-30-A		30'-0"	24" O.D. x .469" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-40-32-A		32'-0"	24" O.D. x .500" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-40-34-A		34'-0"	24" O.D. x .500" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-40-36-A		36'-0"	24" O.D. x .562" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-40-26-B		26'-9"	24" O.D. x .344" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-28-B		28'-0"	24" O.D. x .375" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-30-B		30'-0"	24" O.D. x .375" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-32-B		32'-0"	24" O.D. x .375" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-34-B		34'-0"	24" O.D. x .406" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-36-B		36'-0"	24" O.D. x .406" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-32-C		32'-0"	24" O.D. x .562" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-40-32-D		32'-0"	24" O.D. x .438" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-28-E		28'-9"	24" O.D. x .625" THK.	4.5" O.D. x .203" THK.	2.375" O.D. x .154" THK.
C-40-30-E		30'-0"	24" O.D. x .625" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-40-32-E		32'-0"	24" O.D. x .625" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-40-34-E		34'-0"	24" O.D. x .75" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-40-36-E		36'-0"	24" O.D. x .75" THK.	4.5" O.D. x .237" THK.	2.375" O.D. x .154" THK.
C-40-26-F		26'-9"	24" O.D. x .438" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-28-F		28'-0"	24" O.D. x .469" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-30-F		30'-0"	24" O.D. x .469" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-32-F		32'-0"	24" O.D. x .5" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-34-F		34'-0"	24" O.D. x .5" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.
C-40-36-F		36'-0"	24" O.D. x .562" THK.	4.5" O.D. x .237" THK.	1.9" O.D. x .145" THK.

NOTE:

SEE APPROPRIATE 800 SERIES STANDARD FOR BOX TRUSS
CANTILEVER SIGN STRUCTURE ELEVATION VIEW.

SPECIFICATION 803	CATEGORY CODE ITEMS		Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES BOX TRUSS CANTILEVER SIGN STRUCTURES DESIGN / STRUCTURE DATA		
APPROVED	 DIRECTOR - OFFICE OF TRAFFIC AND SAFETY				
 State Highway Administration	APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION			
	APPROVAL 8-12-02	APPROVAL 9-4-02			
	REVISED	REVISED			
REVISED	REVISED				
REVISED	REVISED				
			STANDARD NO.		MD 803.06-01