


REINFORCEMENT:

VERTICAL SHALL BE NO.4 BARS BENT AND SPACED AT 18" C/C. HORIZONTAL SHALL BE 2 CONTINUOUS NO.5 BARS SPACED AS SHOWN.

**TYPICAL SECTION**

TO BE USED WHEN THE BARRIER IS FUNCTIONING AS A RETAINING WALL AT THE BOTTOM OF THE CUT OR FILL SLOPES.
(SEE STD. MD 648.52 FOR 42" F SHAPE CONCRETE TRAFFIC BARRIER SINGLE FACE TYPE 1 WITH EARTH BACKING AT TOP OF FILL SLOPES)
(SEE STD. MD 648.53 FOR 42" F SHAPE CONCRETE TRAFFIC BARRIER SINGLE FACE TYPE 2 FREE STANDING AT TOP OF FILL SLOPES)

NOTES

1. THE BARRIER AND FOOTER SHALL BE CAST SEPARATELY USING THE FIXED FORM OR THE SLIP FORM CONSTRUCTION METHOD USING CONCRETE MIX NO.6 CONTINUOUSLY PLACED.
2. THE CONTRACTOR HAS THE OPTION TO CONSTRUCT THE BARRIER FOOTER AND BARRIER AFTER CONSTRUCTION OF THE PAVEMENT. THE FOOTER FORMS, IF USED, SHALL BE REMOVED BEFORE PLACING PAVEMENT.
3. ALL REINFORCEMENT BARS, INCLUDING ENDS, SHALL BE EPOXY COATED. ALL BAR LAPS TO BE 30 BAR DIAMETERS. TIE BARS TOGETHER. ALL BARS SHALL BE ASTM A 615 GRADE 60.
4. THE REAR VERTICAL WALL SHALL BE FORMED OR THE CONCRETE PLACED AGAINST THE VERTICAL EARTH SIDE IF APPROVED BY THE ENGINEER. NO ADDITIONAL COMPENSATION FOR ADDITIONAL CONCRETE WILL BE PAID IF CONCRETE IS PLACED AGAINST THE EARTH. THE BARRIER FOOTER SHALL HAVE CONSTRUCTION JOINTS TO COINCIDE WITH THE BARRIER JOINTS.
5. LIMITS OF EXCAVATION: WHEN THE BARRIER IS AT THE BOTTOM OF A CUT SLOPE THE EXCAVATION LIMITS SHALL BE THE LINES INDICATING THE BARRIER FOOTER AND A VERTICAL LINE EXTENDING FROM THE HEEL OF THE FOOTER TO ITS INTERSECTION WITH THE CUT SLOPE. WHEN THE BARRIER IS AT THE TOE OF A FILL SLOPE THE EXCAVATION LIMITS SHALL BE THE LINES INDICATING THE BARRIER FOOTER.
6. SPACING OF CONSTRUCTION JOINTS SHALL BE 20 FEET REGARDLESS OF THE CONSTRUCTION METHOD.
7. COST OF THE CONCRETE FOOTER (FORMED OR NON-FORMED), REINFORCEMENT, DRAINAGE APPURTENANCES, EXCAVATION, GEOTEXTILE, AND BACKFILLING USING SELECT BORROW SHALL BE INCIDENTAL TO THE CONTRACT UNIT PRICE PER LINEAR FOOT FOR 42 INCH F SHAPE CONCRETE TRAFFIC BARRIER SINGLE FACE TYPE 3.
8. TOLERANCES IN DIMENSIONS SHOWN SHALL BE WITHIN 1/4".
9. CONDUIT: IF REQUIRED REFER TO STD. MD 648.50.
10. WHEN BARRIER IS CONSTRUCTED USING THE SLIP FORM METHOD DIAGONAL NO.4 BARS ARE REQUIRED. SEE STD. MD 648.49.

SPECIFICATION 604	CATEGORY CODE ITEMS										
APPROVED <i>Kirk G. McCall</i> DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT											
SHA State Highway Administration	<table><tr><td>APPROVAL • SHA REVISIONS</td><td>APPROVAL • FEDERAL HIGHWAY ADMINISTRATION</td></tr><tr><td>APPROVAL 3-1-01</td><td>APPROVAL 3-28-01</td></tr><tr><td>REVISED 2-10-04</td><td>REVISED 3-31-04</td></tr><tr><td>REVISED</td><td>REVISED</td></tr><tr><td>REVISED</td><td>REVISED</td></tr></table>	APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION	APPROVAL 3-1-01	APPROVAL 3-28-01	REVISED 2-10-04	REVISED 3-31-04	REVISED	REVISED	REVISED	REVISED
APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION										
APPROVAL 3-1-01	APPROVAL 3-28-01										
REVISED 2-10-04	REVISED 3-31-04										
REVISED	REVISED										
REVISED	REVISED										

Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES
**42 INCH F SHAPE CONCRETE TRAFFIC
BARRIER SINGLE FACE TYPE 3
(BOTTOM OF CUT OR TOE OF FILL)**

STANDARD NO. MD 648.54