



| STRUCTURE MARK | SPAN S _D | HEIGHT H _D | TOWER POLE SIZE | TOWER BRACING TUBE SIZE | TRUSS CHORD TUBE SIZE |
|----------------|---------------------|-----------------------|----------------------|-------------------------|------------------------|
| OH-125-28A | 125'-0" | 28'-9" | 20"O.D. x .281" THK. | 8.625"O.D. x .25" THK. | 8.625"O.D. x .25" THK. |
| OH-125-30A | | 30'-0" | 20"O.D. x .281" THK. | 8.625"O.D. x .25" THK. | 8.625"O.D. x .25" THK. |
| OH-125-32A | | 32'-0" | 20"O.D. x .281" THK. | 8.625"O.D. x .25" THK. | 8.625"O.D. x .25" THK. |
| OH-125-34A | | 34'-0" | 20"O.D. x .312" THK. | 8.625"O.D. x .25" THK. | 8.625"O.D. x .25" THK. |
| OH-125-36A | | 36'-0" | 20"O.D. x .312" THK. | 8.625"O.D. x .25" THK. | 8.625"O.D. x .25" THK. |
| OH-125-28B | 125'-0" | 26'-9" | 16"O.D. x .312" THK. | 6.625"O.D. x .28" THK. | 6.62"O.D. x .25" THK. |
| OH-125-30B | | 28'-0" | 16"O.D. x .312" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-125-32B | | 30'-0" | 16"O.D. x .312" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-125-34B | | 32'-0" | 16"O.D. x .344" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-125-36B | | 34'-0" | 16"O.D. x .375" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-130-28A | 130'-0" | 28'-9" | 20"O.D. x .281" THK. | 8.625"O.D. x .25" THK. | 8.625"O.D. x .25" THK. |
| OH-130-30A | | 30'-0" | 20"O.D. x .281" THK. | 8.625"O.D. x .25" THK. | 8.625"O.D. x .25" THK. |
| OH-130-32A | | 32'-0" | 20"O.D. x .312" THK. | 8.625"O.D. x .322" THK. | 8.625"O.D. x .25" THK. |
| OH-130-34A | | 34'-0" | 20"O.D. x .312" THK. | 8.625"O.D. x .25" THK. | 8.625"O.D. x .25" THK. |
| OH-130-36A | | 36'-0" | 20"O.D. x .344" THK. | 8.625"O.D. x .25" THK. | 8.625"O.D. x .25" THK. |
| OH-130-28B | 130'-0" | 26'-9" | 16"O.D. x .312" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-130-30B | | 28'-0" | 16"O.D. x .312" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-130-32B | | 30'-0" | 16"O.D. x .312" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-130-34B | | 32'-0" | 16"O.D. x .344" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-130-36B | | 34'-0" | 16"O.D. x .375" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-135-28A | 135'-0" | 28'-9" | 20"O.D. x .281" THK. | 8.625"O.D. x .28" THK. | 8.625"O.D. x .25" THK. |
| OH-135-30A | | 30'-0" | 20"O.D. x .312" THK. | 8.625"O.D. x .322" THK. | 8.625"O.D. x .25" THK. |
| OH-135-32A | | 32'-0" | 20"O.D. x .312" THK. | 8.625"O.D. x .322" THK. | 8.625"O.D. x .25" THK. |
| OH-135-34A | | 34'-0" | 20"O.D. x .312" THK. | 8.625"O.D. x .322" THK. | 8.625"O.D. x .25" THK. |
| OH-135-36A | | 36'-0" | 20"O.D. x .344" THK. | 8.625"O.D. x .322" THK. | 8.625"O.D. x .25" THK. |
| OH-135-28B | 135'-0" | 26'-9" | 16"O.D. x .312" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-135-30B | | 28'-0" | 16"O.D. x .312" THK. | 6.625"O.D. x .28" THK. | 8.62"O.D. x .25" THK. |
| OH-135-32B | | 30'-0" | 16"O.D. x .344" THK. | 8.625"O.D. x .322" THK. | 8.62"O.D. x .25" THK. |
| OH-135-34B | | 32'-0" | 16"O.D. x .375" THK. | 8.625"O.D. x .322" THK. | 8.62"O.D. x .25" THK. |
| OH-135-36B | | 34'-0" | 16"O.D. x .406" THK. | 8.625"O.D. x .322" THK. | 8.62"O.D. x .25" THK. |
| OH-140-28A | 140'-0" | 28'-9" | 18"O.D. x .375" THK. | 8.625"O.D. x .322" THK. | 8.625"O.D. x .25" THK. |
| OH-140-30A | | 30'-0" | 18"O.D. x .375" THK. | 8.625"O.D. x .322" THK. | 8.625"O.D. x .25" THK. |
| OH-140-32A | | 32'-0" | 20"O.D. x .312" THK. | 8.625"O.D. x .322" THK. | 8.625"O.D. x .25" THK. |
| OH-140-34A | | 34'-0" | 20"O.D. x .344" THK. | 8.625"O.D. x .322" THK. | 8.625"O.D. x .25" THK. |
| OH-140-36A | | 36'-0" | 20"O.D. x .375" THK. | 8.625"O.D. x .322" THK. | 8.625"O.D. x .25" THK. |
| OH-140-28B | 140'-0" | 26'-9" | 16"O.D. x .312" THK. | 8.625"O.D. x .322" THK. | 8.62"O.D. x .25" THK. |
| OH-140-30B | | 28'-0" | 16"O.D. x .344" THK. | 8.625"O.D. x .322" THK. | 8.62"O.D. x .25" THK. |
| OH-140-32B | | 30'-0" | 16"O.D. x .344" THK. | 8.625"O.D. x .322" THK. | 8.62"O.D. x .25" THK. |
| OH-140-34B | | 32'-0" | 16"O.D. x .375" THK. | 8.625"O.D. x .322" THK. | 8.62"O.D. x .25" THK. |
| OH-140-36B | | 34'-0" | 16"O.D. x .406" THK. | 8.625"O.D. x .322" THK. | 8.62"O.D. x .25" THK. |

NOTE:

REFER TO APPROPRIATE 800 SERIES STANDARD PLATE REGARDING OVERHEAD SPAN SIGN STRUCTURE ELEVATION VIEW.

| | |
|---|--|
| SPECIFICATION 803 | CATEGORY CODE ITEMS |
| APPROVED |  DIRECTOR - OFFICE OF TRAFFIC AND SAFETY |
|  | APPROVAL • SHA REVISIONS |
| | APPROVAL 8-12-02 |
| | REVISED |
| | REVISED |
| | APPROVAL • FEDERAL HIGHWAY ADMINISTRATION |
| | APPROVAL 9-4-02 |
| | REVISED |
| | REVISED |

**Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES
OVERHEAD SPAN SIGN STRUCTURES
DESIGN / STRUCTURE DATA**

STANDARD NO.

MD 803.08-11