



FOUNDATION DETAIL SCHEDULE				
FOOTING MARK	FOOTING DIMENSION		CUBIC YARDS CONCRETE	
	W	Y	TYPE A	TYPE B
OF-420	4'-0"	20'-0"	19.4	22.2
OF-421	4'-0"	21'-0"	20.1	22.9
OF-422	4'-0"	22'-0"	20.9	23.6
OF-423	4'-0"	23'-0"	21.5	24.3
OF-424	4'-0"	24'-0"	22.3	25.1
OF-425	4'-0"	25'-0"	23.0	25.8
OF-426	4'-0"	26'-0"	23.8	26.6
OF-427	4'-0"	27'-0"	24.5	27.3
OF-620	6'-0"	20'-0"	29.2	34.8
OF-621	6'-0"	21'-0"	30.3	35.9
OF-622	6'-0"	22'-0"	31.4	37.0
OF-623	6'-0"	23'-0"	32.5	38.1
OF-624	6'-0"	24'-0"	33.7	39.3
OF-625	6'-0"	25'-0"	34.8	40.4
OF-626	6'-0"	26'-0"	35.9	41.5

NOTES:

1. CONCRETE QUANTITIES SHOWN ARE BASED ON MINIMUM DIMENSIONS. ACTUAL QUANTITIES WILL BE AS SPECIFIED IN THE ERECTION DRAWINGS OF CONTRACT DOCUMENTS.
2. FOR FOOTING DETAILS, REFER TO APPROPRIATE 800 SERIES STANDARD PLATE.

SPECIFICATION 803	CATEGORY CODE ITEMS
APPROVED	 DIRECTOR - OFFICE OF TRAFFIC AND SAFETY
	APPROVAL • SHA REVISIONS
	APPROVAL 8-12-02
	REVISED
	REVISED
	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION
	APPROVAL 9-4-02
	REVISED
	REVISED

Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
 STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES
OVERHEAD SPAN SIGN STRUCTURES FOUNDATION
DATA FOR TYPE 'A' AND TYPE 'B'
STANDARD NO. MD 803.08-23