CONCRETE BARRIER MOUNTED SIGN (MAXIMUM SIGN AREA - 40 SQ. FT.) POST CAP MAX DETAIL 'B' 0 STIFFNERS SHALL BE INSTALLED AT 30" MAXIMUM SPACING Го ,0 MAX o -SEE DETAIL "B" FOR SIGNS OVER 30" WIDTH. o DETAIL 'A' REFER TO APPROPRIATE 800 SERIES-STANDARD PLATE FOR CAST-IN-PLACE INSTALLATION ON NEW CONCRETE BARRIERS. REFER TO APPROPRIATE 800 SERIES. STANDARD PLATE FOR SIGN SUPPORT ANCHORAGE ON EXISTING CONCRETE BARRIERS. MIN. (DOUBLE VARIES ROAD SHOULDER **DETAIL 'B' - TOP VIEW** (TUBULAR STEEL POST) 1/4" x 1" BOLTS. NUTS AND יב" DIA. BOLT WITH LOCK. NUTS. WASHER (S.S. TYPE 304) FLAT WASHERS (S.S. TYPE 304) — SIGN PANEL MAX. 4" TYP. .3" x 14" GALVANIZED STEEL BAR — TS 6″ × 4″ × ³⁄8″ GALVANIZED POST SPECIFICATION CATEGORY CODE ITEMS **Maryland Department of Transportation** 813 STATE HIGHWAY ADMINISTRATION **APPROVED** STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES DIRECTOR - OFFICE OF TRAFFIC AND SAFETY APPROVAL . SHA APPROVAL . FEDERAL SPECIAL SIGN SUPPORTS REVISIONS HIGHWAY ADMINISTRATION **CONCRETE BARRIER MOUNTED SIGN** APPROVAL 2-21-95 APPROVAL 2-21-95 10-1-01 2-1-01 REVISED StateHighway MD 813.09-01 STANDARD NO.