


RAMP DELINEATION



LOOP RAMP

NON-LOOP RAMP

- LEGEND**
- SINGLE YELLOW
 - SINGLE WHITE
 - ⊖ DOUBLE WHITE

RAMP MARKERS AND DELINEATORS SHALL BE PLACED ON

- THE RIGHT SIDE OF TANGENT SECTIONS
- THE OUTSIDE OF CURVED SECTIONS
- * - BOTH SIDES OF THE RAMP (THREE INSTALLATIONS) WHERE THE CURVE ENTERS A TANGENT SECTION OR REVERSES

RAMP DELINEATOR SPACING

- SPACING SHOULD BE AS SPECIFIED IN MUTCD TABLE 111-1.

SPECIFICATION 604, 605	CATEGORY CODE ITEMS
APPROVED <i>Kirk G. McCall</i> DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT	
	APPROVAL • SHA REVISIONS
	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION
	APPROVAL 7-1-94
	REVISED 11-08-06
	REVISED 10-25-06

**Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION**
STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

RAMP DELINEATION

STANDARD NO. MD 665.06