



- NOTES:
1. FOR ARROW DIMENSIONS REFER TO ARROWDET-1.
  2. SIGN SHALL BE SINGLE FACE ONLY.
  3. FOR MAST ARM USE ONLY.

- \* MAXIMUM WIDTH - 96" STD, 120" OVERSIZED
- \*\* CLEARVIEW TYPE SYSTEM: CLEARVIEWHWY-2-W
- \*\*\* CLEARVIEW TYPE SYSTEM: CLEARVIEWHWY-3-W

SIGN SIZE	DIMENSIONS (INCHES)									
	A	B	C	D	E	F	G	H	J	K
STD	VAR*	16	3/4	4	8**	3-1/4	4***	3-5/16	9-3/8	3-1/4 MIN
OVERSIZED	VAR*	20	1-1/8	4.7	10.6**	4	5***	3-3/8	13-1/4	4 MIN
DUAL PANEL STD	VAR*	32	3/4	---	---	---	4***	3-1/2	9-3/8	3-1/4 MIN
DUAL PANEL OVERSIZED	VAR*	40	1-1/8	---	---	---	5***	3-21/32	13-1/4	4 MIN

SIGN SIZE	DIMENSIONS (INCHES)									
	L	M	N	P	Q	R	S	T	U	
STD	10-5/8	4 MIN	6 MIN	1-7/8	---	---	---	---	---	
OVERSIZED	14-3/4	4 MIN	6 MIN	3	---	---	---	---	---	
DUAL PANEL STD	10-5/8	4 MIN	6 MIN	1-7/8	4-3/16	8**	3-7/16	3-7/16	8-15/16	
DUAL PANEL OVERSIZED	14-3/4	4 MIN	6 MIN	3	4.98125	10.6**	3.85625	4-9/32	11-9/32	

REFERENCES

MD MUTCD SECTION - 2D.38

COLORS

LEGEND - WHITE

BACKGROUND - GREEN

APPROVED Tom Hicks (signature on file)  
DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

**Maryland Department of Transportation**  
**STATE HIGHWAY ADMINISTRATION**  
MARYLAND STANDARD HIGHWAY SIGNS  
**OVERHEAD STREET NAME PANEL**



APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION
APPROVAL 03/02/2009	APPROVAL
REVISED	REVISED
REVISED	REVISED
REVISED	REVISED

SIGN NUMBER

D-3(1)