



NOTES:

- SPECIAL SIGNS MAY BE REQUESTED FROM THE SHA SIGN SHOP. THEY SHOULD BE SPECIFIED BY HEIGHT, TO DETERMINE WHAT BASIC DIMENSIONS ARE UTILIZED, AND LENGTH, IF KNOWN, TO COINCIDE WITH ADDITIONAL PANELS OF THE SAME ASSEMBLY, OR DUE TO RIGHT-OF-WAY CONSTRICTIONS, ETC. IF LENGTH IS UNKNOWN AND RIGHT-OF-WAY IS CRITICAL, SPECIFY LENGTH AS MAXIMUM AND THE SIGN WILL BE FABRICATED AS SHOULD BE APPREVIATED TO ACCOMMODATE MESSACES.
- 2. WHERE APPLICABLE, NAMES SHOULD BE ABBREVIATED TO ACCOMMODATE MESSAGES
- WHERE APPLICABLE, NAMES SHOULD BE ABBREVIATED TO ACCOMMODATE MESSAGES ON STANDARD LENGTH PANELS.
 MILEAGE SHALL NOT BE SHOWN ON DESTINATION PANELS.
 WHEN MULTI-DIRECTIONAL PANELS ARE USED IN THE SAME ASSEMBLY, AS SHOWN, THE STRAIGHT THRU DESTINATION IS PLACED FIRST AT THE TOP, THE LEFT DESTINATION IS SECOND AND THE RIGHT DESTINATION IS PLACED LAST. THERE SHALL BE NO MORE THAN THREE DESTINATION PANELS PER ASSEMBLY.
 FOR ARROW DIMENSIONS REFER TO ARROWDET-I.
 FOR VERTICAL ARROWS, VERTICALLY CENTER ARROW ABOUT "B" DIMENSION. DIMENSIONS "F" AND "C" WILL WARY FROM VALUES IN CHART
- "F" AND "G" WILL VARY FROM VALUES IN CHART.
- * CLEARVIEW TYPE SYSTEM: CLEARVIEWHWY-2-W

SIGN	DIMENSIONS (INCHES)								
SIZE	А	В	С	D	E	F	G	Н	J
MIN	VAR	12	1/2	3	6*	2-5/8	6-3/4	4	1- 1/2
STD	VAR	12	1/2	3	6*	2-5/8	6-3/4	4	1- 1/2
EXPWY (MIN)	VAR	16	3/4	4	8*	3-5/16	9-3/8	6	I- 7/8
EXPWY	VAR	16	3/4	4	8*	3-5/16	9-3/8	6	I- 7/8

REFERENCES

MdMUTCD SECTION - 2D.34, 2D.35

COLORS

LEGEND - WHITE

BACKGROUND - GREEN

APPROVED

Tom Hicks (signature on file)

DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

CUA	APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION		
	APPROVAL 03/02/2009	APPROVAL		
	REVISED	REVISED		
StateHighwav	REVISED	REVISED		
Administration	REVISED	REVISED		

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

MARYLAND STANDARD HIGHWAY SIGNS

DESTINATION PANELS

SIGN NUMBER

D1-1(1)