

500 FT ^{|F|} _A

1000 FT ^{|G|} _B

1 MILE ^{|H|} _C _A

1/2 MILE ^{|J|} _D _E

1500 FT ^{|K|} _B

AHEAD _A

NOTE: "C" LETTERS MAY BE SUBSTITUTED FOR "D" LETTERS ONLY WHEN "D" LETTERS DO NOT FIT.

* SPACING REDUCED BY 40%
 ** SPACING REDUCED BY 50%

DIMENSIONS (INCHES)									
A	B	C	D	E	F	G	H	J	K
5C	5C*	7.5C	7.5C**	5C**	1.79	2.7	1.83	1.6	2.86
6C	6C*	9C	9C**	6C**	1.95	3.24	2.15	1.9	3.43
7C	7C*	10.5C	10.5C**	7C**	2.11	3.78	2.46	2.2	4
8C	8C*	12C	12C**	8C**	2.51	4.32	2.78	2.4	4.57
--	--	--	13.5C**	9C**	--	--	--	2.6	--
4D	4D*	6D	6D**	4D**	1.56	1.45	1.69	1.5	1.57
5D	5D*	7.5D	7.5D**	5D**	2.01	2.81	3.14	1.8	2.97
6D	6D*	9D	9D**	6D**	2.34	2.17	4.6	2	2.36
7D	7D*	10.5D	10.5D**	7D**	2.79	2.53	3.93	2.2	2.75
8D	8D*	12D	12D**	8D**	3.12	2.89	3.38	2.4	3.15
9D	9D*	13.5D	13.5**	9D**	4.45	4.13	4.46	2.6	4.42
10D	10D*	15D	15D**	10D**	6.52	6.12	6.29	2.8	6.43

REFERENCES

MdMUTCD SECTION - NONE

COLORS

LEGEND - BLACK

APPROVED Tom Hicks (signature on file)
 DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
 MARYLAND STANDARD HIGHWAY SIGNS



APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION
APPROVAL 03/02/2009	APPROVAL
REVISED	REVISED
REVISED	REVISED
REVISED	REVISED

DISTANCE DETAILS

SIGN NUMBER

DISTANCE DETAILS