

NOTES:

I. ARROWDET-2 AND ROUNDABOUT ARROW FOR LEFT SIDE USE ONLY.

2. "M6-I" AND "ARROWDET-2" SIGN -- FOR ARROW DIMENSIONS AND DETAILS REFER TO M6-I, M6-I(I) AND ARROWDET-2.

3. "ROUNDABOUT" SIGN -- FOR ARROWHEAD DIMENSIONS REFER TO STANDARD ARROW DETAILS IN APPENDIX-ARROWS SECTION FROM FHWA'S STANDARD HIGHWAY SIGNS BOOK-APPENDIX (SCALE DOWN DETAILS FOR ARROWHEAD DIMENSIONS).

* IF NUMERALS DO NOT FIT USING 'D' SERIES, 'C' SERIES MAY BE USED ** 12D CAN BE USED IF THE NUMBER HAS A "I"

SIGN	DIMENSIONS (INCHES)										
SIZE	А	В	С	D	Е	F	G	Н	J	K	L
STD (I-2 DIGIT) M6-I	24	72	1/2	3	8/6B	3	7	6-1/4	1-1/2	1-5/8	12D*
STD (I-2 DIGIT) ARROWDET-2	24	72	1/2	3	8/6B	2-15/16	7-1/8	6-1/4	1-1/2	1-5/8	12D*
STD (I-2 DIGIT) ROUNDABOUT	24	72	1/2	3	8/6B	2-3/16	8-5/8	6-1/4	1-1/2	1-5/8	12D*
STD (3 DIGIT) M6-I	30	72	1/2	3	8/6C	3	7	6-1/4	1-1/2	1-5/8	12C**
STD (3 DIGIT) ARROWDET-2	30	72	1/2	3	8/6C	2-15/16	7-1/8	6-1/4	1-1/2	1-5/8	12C**
STD (3 DIGIT) ROUNDABOUT	30	72	1/2	3	8/60	2-3/16	8-5/8	6-1/4	1-1/2	1-5/8	120**

SIGN	DIMENSIONS (INCHES)										
SIZE	М	Ν	Р	Q	R	S	Т	U	V	W	Χ
STD (I-2 DIGIT) M6-I	2-1/2	7	3-1/2						2-5/8		
STD (I-2 DIGIT) ARROWDET-2	2-1/2	7	3-1/2						2-5/8		
STD (I-2 DIGIT) ROUNDABOUT	2-1/2	7	3-1/2	3-3/4	4-7/8	1-3/4	7-1/2	1-7/8	1-1/4	3/4	3-3/4
STD (3 DIGIT) M6-I	2-1/2	7	3-1/2						2-5/8		
STD (3 DIGIT) ARROWDET-2	2-1/2	7	3-1/2						2-5/8		
STD (3 DIGIT) ROUNDABOUT	2-1/2	7	3-1/2	3-3/4	4-7/8	1-3/4	7-1/2	1-7/8	1-1/4	3/4	3-3/4

REFERENCES

MdMUTCD SECTION - 2D.10, 2D.11, 2D.27, 2D.30

COLORS

LEGEND - BLACK

BACKGROUND - WHITE

APPROVED

Tom Hicks (signature on file)

DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

	APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION				
	APPROVAL 03/02/2009	APPROVAL				
	REVISED	REVISED				
StateHighwav	REVISED	REVISED				
Administration	REVISED	REVISED				

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

MARYLAND STANDARD HIGHWAY SIGNS

INTERSECTION DUAL DIRECTIONAL (LIMITED RIGHT-OF-WAY)

SIGN NUMBER

M1-5(5)