



*** FOR ARROWHEAD DIMENSIONS REFER TO ARROWS FOR GUIDE
 SIGNS DOWN-ARROW DETAIL IN APPENDIX-ARROW SECTION FROM
 FWHA'S STANDARD HIGHWAY SIGNS BOOK-APPENDIX SECTION

R3-14

PREFERENTIAL ONLY LANE OPERATION (OVERHEAD)

*Series 2000 Standard Alphabets.
 **Reduce spacing to fit.

	A	B	C	D	E	F	G	H	J	K	L	M	N
C	72	60	1	1.25	14	8 E	4	4	5 D	4	9.5	3.5	15.785
	96	72	1.25	1.5	15	9 E	6	6	7 D	6	10	4	17.819
	144	106	1.5	2	18	16 E	9	9.5	9 D	5	18	5.5	31.75

	P	Q	R	S	T	U	V	W	X	Y
	25.261	11.239	18.613	31	11	4	7.625	1	22	3
	28.356	11.871	21.395	43	15	5	10	1.5	30	4
	50.345	21.5	38.205	64	22	8	15	2	40	6

COLORS: LEGEND — BLACK
 BACKGROUND — WHITE (RETROREFLECTIVE)
 SYMBOL — WHITE (RETROREFLECTIVE ON BLACK)

SHA REFERENCES
 MdMUTCD SECTION - 2B.26, 2B.27, 2B.28, 2E.59