



SHA REFERENCES
MdmUTCD SECTION - 2C.06, 5C.02, 9B.14

W1-4L

SHA REFERENCES
MdmUTCD SECTION - 2C.06, 5C.02, 9B.14

W1-4R

REVERSE CURVE

SHA * FOR ARROWHEAD DIMENSIONS REFER TO STANDARD ARROW
DETAILS IN APPENDIX-ARROWS SECTION FROM FHWA'S
STANDARD HIGHWAY SIGNS BOOK-APPENDIX SECTION.

A	B	C	D	E	F	G	H	J	K	L	M
18	.375	.625	2.375	1	3.875	.25	2.625	8.625	6.25	4	2.625
24	.375	.625	3.156	1.5	5	.313	3.5	11.25	8.25	5.25	3.5
30	.5	.75	3.938	1.875	6.25	.375	4.375	14.063	10.625	6.563	4.375
36	.625	.875	4.719	2.25	7.5	.469	5.25	16.875	12.375	7.875	5.25
48	.75	1.25	6.313	3	10	.625	7	22.5	16.5	10.5	7

N	P	Q
.875	2	1.5
1.125	2.625	1.5
1.406	3.281	1.875
1.688	3.938	2.25
2.25	5.25	3

WARNING SIGN COLORS:

SYMBOL – BLACK

SHA BACKGROUND– FLUORESCENT YELLOW (RETROREFLECTIVE)

TTC SIGN COLORS:

SYMBOL – BLACK

SHA BACKGROUND– FLUORESCENT ORANGE (RETROREFLECTIVE)

C