



SHA REFERENCES
MdMUTCD SECTION - 2C.06, 5C.02, 9B.14

W1-5L

W1-5R

WINDING ROAD

SHA REFERENCES
MdMUTCD SECTION - 2C.06, 5C.02, 9B.14

SHA * FOR ARROWHEAD DIMENSIONS REFER TO STANDARD ARROW
DETAILS IN APPENDIX-ARROWS SECTION FROM FHWA'S
STANDARD HIGHWAY SIGNS BOOK-APPENDIX SECTION.

A	B	C	D	E	F	G	H	J	K	L	M
18	.375	.625	1	9.625	.375	2.5	.625	3	1	4	4
24	.375	.625	1.25	12.75	.5	3.25	.875	4.125	1.25	5.188	5.25
30	.5	.75	1.563	15.938	.625	4.063	1.094	5.156	1.563	6.484	9.563
36	.625	.875	1.875	19.125	.75	4.875	1.313	6.188	1.875	7.781	7.875
48	.75	1.25	2.5	25.5	1	6.5	1.75	8.25	2.5	10.375	10.5

N	P	Q	R	S
8.625	.25	2	1.25	1.5
11.375	.25	2.5	1.598	1.5
14.219	.313	3.125	2	1.875
17.063	.375	3.75	2.406	2.25
22.75	.5	5	3.188	3

COLORS: LEGEND – BLACK
SHA BACKGROUND – FLUORESCENT YELLOW (RETROREFLECTIVE)

C