



SHA



W12-2  
LOW CLEARANCE (ENGLISH)

SHA REFERENCES  
MdMUTCD SECTION - 2C.22

LOW CLEARANCE (METRIC)

A	B	C	D	E	F	G	H	J	K	L	M	N
18	.375	.625	3.438	4	2.125	.5	1.5	1	1.5	.938	.625	.25
30	.5	.75	5.75	6.625	3.75	.75	2.5	1.688	1.875	1.563	1	.438
36	.625	.875	6.875	8	4.25	1	3	2	2.25	1.875	1.25	.5
48	.75	1.25	9.188	10.625	5.875	1.313	4	2.625	3	2.438	1.625	.625

C

P	Q	R	S
1.375	2	3	6 D
2.25	3.313	5	10 D
2.75	4	6	12 D
3.625	5.58	8	16 D

SHA \*FOR ARROWHEAD DIMENSIONS REFER TO ARROWS  
FOR GUIDE SIGNS DOWN-ARROW DETAIL IN  
APPENDIX-ARROW SECTION FROM FHWA'S STANDARD  
HIGHWAY SIGNS BOOK-APPENDIX SECTION  
\*\*Optically space numerals about center line.

WARNING SIGN COLORS:

SYMBOL & LEGEND—BLACK  
SHA BACKGROUND — FLUORESCENT YELLOW  
(RETROREFLECTIVE)

TTC SIGN COLORS:

SYMBOL & LEGEND—BLACK  
SHA BACKGROUND — FLUORESCENT ORANGE  
(RETROREFLECTIVE)